

PRODUCT-DETAILS

ESB24-04-230AC/DC

ESB24-04-230AC/DC Installation Contactor (NC)

24 A - 0 NO - 4 NC - 230 ... 240 V - Control Circuit DC



General Information

Extended Product Type	ESB24-04-230AC/DC
Product ID	GHE3291202R0006
EAN	4013614084546
Catalog Description	ESB24-04-230AC/DC Installation Contactor (NC) 24 A - 0 NO - 4 NC - 230 ... 240 V - Control Circuit DC

Long Description

The ESB24 installation contactor is a 4 pole contactor suitable for modular switchboards. They are specially designed fitting to modular DIN rail products and for applications where customers want to use the panel design with high finger protection. Installation contactors are used in residential, commercial and industrial applications for the control of single or three-phase loads up to 24 A or switching of control signals. Further features are the noiseless and hum-free DC coil, the integrated overvoltage protection up to 5 kV and a switch position indication. Auxiliary contacts, distance pieces and sealing cover for protection against unauthorized changes are available as accessory.

Ordering

Package Level 1 EAN	4013614420535
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Popular Downloads

Data Sheet, Technical Information	2CDC103051C0201
Instructions and Manuals	2CDC103025M6801

Dimensions

Product Net Width	36 mm
Product Net Height	85 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.235 kg

Technical

Rated Operational Voltage	Main Circuit 220 V DC Main Circuit 400 V AC
Rated Control Circuit Voltage (U_c)	230 ... 240 V
Rated Frequency (f)	Control Circuit DC Control Circuit 50 Hz Control Circuit 60 Hz Control Circuit 400 Hz Main Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz
Rated Operational Current AC-1 (I_e)	(NC) 24 A (NO) 24 A
Rated Operational Current AC-3 (I_e)	(230 V) Single Phase 9 A (400 V) Three Phase 9 A
Rated Operational Power AC-1 (P_e)	(230 V) Single Phase 5.5 kW (400 V) Single Phase 16 kW
Rated Operational Power AC-3 (P_e)	(230 V) Single Phase 1.3 kW (400 V) Three Phase 4 kW
Rated Operational Current AC-7a (I_e)	(NC) 24 A (NO) 24 A
Rated Operational Power AC-7a (P_e)	(230 V) Single Phase 5.5 kW (400 V) Three Phase 16 kW
Rated Operational Current AC-7b (I_e)	(230 V) Single Phase 9 A (400 V) Three Phase 9 A
Rated Operational Power AC-7b (P_e)	(230 V) Single Phase 1.3 kW (400 V) Three Phase 4 kW
Recommended Screw Driver	Control Circuit Pozidriv 1 Main Circuit Pozidriv 1
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 500 V
Connecting Capacity Main	Flexible with Ferrule 1x 1.5 ... 10 mm ²

Circuit	Flexible with Insulated Ferrule 1x 1.5 ... 10 mm ² Flexible 1x 1.5 ... 10 mm ² Rigid 1x 1.5 ... 10 mm ² Rigid 2x 4 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Ferrule 2x 0.75 ... 1 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible 1x 1 ... 4.0 mm ² Flexible 2x 1 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ² Rigid 2x 2.5 mm ²
Tightening Torque	Control Circuit 0.9 N·m Main Circuit 1 N·m
Wire Stripping Length	Control Circuit 7 mm Main Circuit 10 mm
Degree of Protection	IP20
Electrical Durability	AC-1 150000 cycle AC-3 500000 cycle AC-7a 150000 cycle AC-7b 500000 cycle
Mechanical Durability	1000000 cycle
Number of Poles	4
Number of Auxiliary Contacts NO	0
Number of Main Contacts NC	4
Number of Main Contacts NO	0
Width in Number of Modular Spacings	2
Pollution Degree	3
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 IEC/EN 61095 UL 60947-1 UL 60947-4-1
Remarks	Installation contactor, noiseless/humfree, high insulation, reliable function, long life

Technical UL/CSA

Horsepower Rating UL/CSA	(220 ... 240 V AC) Single Phase 3 Hp (440 ... 480 V AC) Three Phase 5 Hp
Connecting Capacity Main Circuit UL/CSA	Stranded 16-8 AWG
Connecting Capacity Control Circuit UL/CSA	Stranded 16-10 AWG
Tightening Torque UL/CSA	Control Circuit 8 in·lb Main Circuit 9 in·lb

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C
-------------------------	--------------------------

	Storage -40 ... +80 °C
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 15g
Resistance to Vibrations	5g 3 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Material Compliance

REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Consumer
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

BV Certificate	1SAA920000-0204
CB Certificate	1SAA920000-2003
CQC Certificate	CQC2003010304064076
Declaration of Conformity - CCC	2020980304001308
Declaration of Conformity - CE	1SAD938513-0007
DNV Certificate	1SAA920000-0306
EAC Certificate	1SAA920000-2702
KC Certificate	1SAA920001-1501
RMRS Certificate	1SAA920000-0705
UL Certificate	E191658-19960301

Container Information

Package Level 1 Units	5 piece
Package Level 1 Width	89 mm
Package Level 1 Height	69 mm
Package Level 1 Depth / Length	183 mm
Package Level 1 Gross Weight	1.22 kg
Package Level 1 EAN	4013614420535

Classifications

Object Classification Code	Q
----------------------------	---

ETIM 4	EC001653 - Installation contactor for distribution board
ETIM 5	EC001653 - Installation contactor for distribution board
ETIM 6	EC001653 - Installation contactor for distribution board
ETIM 7	EC001653 - Installation contactor for distribution board
eClass	V11.0 : 27142308
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4759 >> Installation contactor for distribution board
E-Number (Finland)	3709412
ETIM 8	EC001653 - Installation contactor for distribution board

Categories

Low Voltage Products and Systems → Control Products → Contactors → Installation Contactors

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling Devices → Installation Contactors

