Product data sheet Characteristics

SDN0200160

Sedna - 2 poles switch - 10AX, without frame, aluminium





Main

IVIAIII		C C
Range name	Sedna	
Range	Sedna	ij
Product or component type	Push-button	
Function	1-pole 2-way push-button	,
Delivery form	Without frame	- Local distribution of the control
Rated current	10 A - 250 V AC	ה ה פ פ
Rocker color	Beige	
Marking	Without marking	eff id
Kind of terminals	Screwless terminals	<u> </u>

Complementary

Pilot light	Blue locator lamp	Pos
Power range	2300 W	94
Installation	Flush	not to
Terminal capacity	2 x 2.5 mm²	and is
Wire structure	Flexible Rigid	itute for
Wire stripping length	12 mm	subst
Material of visible parts	Thermoplastic ABS-UV stabilised	as a
Surface finish	Glossy	pape
Fixing mode	Claws, span of claws working range : 5180 mm Screws	not inter
Height	71 mm	ion is
Width	71 mm	entat
Depth	42 mm	OCHIT
Depth of visual part	12 mm	hisd
Product weight	0.07764 kg	mer

Environment

Standards	IEC 60669-1
Conformity mark	CE
Product certifications	GOST-R
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1715 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
	Product Environmental Profile	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period	18 months