



## KABELSCHLEPP cable carrier



order key: **0555.050.100.063-999**

quantity : **1**

### dimensions

chain length Lk:	999	mm
pitch:	55.50	mm
number of links n (incl. n reserve = ) :	18	
number of stays nSt:	18	
inner width Bi:	100	mm
outer width Bk:	122	mm
inside height hi:	38.00	mm
link height hG:	50.00	mm
bending radius KR:	63.00	mm
self weight of chain :	1.98	kg/m
self weight of chain total:	2	kg
:		standard

### end connectors

driver connection:	with
connection of fixed point:	with

### application parameters

arrangement:	given chain length Lk	
given chain length Lk:	1000.00	mm
connection height H':	150.00	mm
total height H:	176.00	mm
weight of cables qz	0.10	kg/m
max. acceleration a	1.00	m/s <sup>2</sup>

max. velocity v

1.00 m/s

frequency

100 / h

© 2022 TSUBAKI KABELSCHLEPP GmbH, Wenden-Gerlingen

# GIVING LIFE 2 PRODUCTS

HELLO@EXSTOCK2USER.COM

+971504768737

Q INDUSTRIAL E-MARKETPLACE

STOCKIST, DISTRIBUTORS  
& TRADERS

ELECTRONICS | ELECTRICAL | AUTOMATION | MECHANICAL | INSTRUMENTATION | SOLAR | HVAC