



Electric Automation
Automation specialists

Reference: DDA202A-40/0,03
Code: 2CSB202101R1400

DDA202 A-40/0,03 - RCD Block

Buy it at Electric Automation Network



The RCD block DDA200 series is suitable for assembly with MCBs S200 series. It assures protection against the effects of sinusoidal alternating and direct pulsating earth fault currents, protection, against indirects contacts and additional protection against direct (with sensitivity = 30 mA) contacts. Applications: residential, commercial, industrial.

Ordering

EAN:	8012542795506
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363030

Dimensions

Product Net Width:	0.070 m
Product Net Height:	0.093 m
Product Net Depth:	0.069 m
Product Net Weight:	0.210 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.077 m

Package Level 1 Height:	0.076 m
Package Level 1 Length:	0.102 m
Package Level 1 Gross Weight:	0.245 kg
Package Level 1 EAN:	8012542795513

Technical

Standards:	EN 61009 Ann. G
Operating Characteristic:	Instantaneous
Type of Residual Current:	A type
Rated Residual Current:	30 mA
Rated Current (I_n):	40 A
Number of Poles:	2
Power Loss:	3.2 W
Rated Voltage (U_r):	230/400 V

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q3
--------------	---

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	ITSCE127DDA200
RoHS Information:	2CSC427001K0201

Classifications

Object Classification Code:	Q
ETIM 4:	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 5:	EC002297 - Residual current circuit breaker (RCCB) module