## Catalogue No: 2711R-T4T

## PV800 4.3in TFT TOUCH COLOR ENET SERIAL 24VDC

Automation Systems > Operator Panels and Industrial Computers > Micro Operator Panels > Allen-Bradley® PanelView™ 800 Graphic Terminals > Terminals





PanelView 800 4.3 inch HMI, Touch Screen Serial and Ethernet ports

- Optimized for compatibility with Micro800® and MicroLogix™ controllers
- Includes high-resolution display with LED backlight supporting 65K colours
- Offers flexible application modes in landscape and portrait
- Includes high performance 800MHz processor with 128MB / 256MB memory
- Includes USB host port and microSD™ support file transfer or updating firmware
- Alerts operators with alarm messages that include embedded variables
- Provides ability to upload and download groups of data or parameter settings with recipe capability

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Product Series	PanelView 800 (Bul. 2711R)
Power Supply	24V DC
Power Consumption (Max.)	9 W(DC) / VA(AC)
Operator Input Method(s)	Touch
Display Size	4 inches
Display Resolution	480x272 pixels
Display Colours	65 k
Display Backlight	LED
Display Backlight Life	40000 hours
Real Time Clock	Integrated
Ethernet Interfaces	1 x 10/100Mbps
Height	116 mm
Width	138 mm
Depth	43 mm
Height, Cutout	99 mm
Width, Cutout	119 mm
Ambient temperature, max	50 °C
Software, Configuration	Connected Components Workbench



## Catalogue No: 2711R-T4T

## PV800 4.3in TFT TOUCH COLOR ENET SERIAL 24VDC

Automation Systems > Operator Panels and Industrial Computers > Micro Operator Panels > Allen-Bradley® PanelView $^{\text{TM}}$  800 Graphic Terminals > Terminals



REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-